

## 永磁滑轮





型号 | KPR

产地 | 日本·Kanetec

### 产品描述

**用途** 广泛应用于化工、炼铁、煤炭、食品、矿山等行业的粉粒状物料的垃圾处理系统和除铁

**特点**

- 磁力强大持久
- 无需电源即可产生磁力
- 结构坚固，操作和安装方便
- 易于集成到带式输送机 and 现有生产线中
- 高磁通密度，进一步提高铁和弱磁性物质的回收率。

# 规格参数

型号	皮带宽度	外形尺寸								表面最大磁
		$\phi D$	B	L	$d_1$	$d_2$	$L_1$	$L_2$	键槽	密度
KPR-H1635	350	160	440	670	60	-	100	-	20x10	1.3T(13000 G)以上
KPR-H1640	400	160	500	730	60	-	100	-	20x10	
KPR-H1645	450	160	550	780	60	-	100	-	20x10	
KPR-2230	300	214	350	660	40	35	130	50	10x5	80mT(800G)以上
KPR-2235	350	214	400	710	40	35	130	50	10x5	
KPR-2240	400	214	450	760	40	35	130	50	10x5	
KPR-2735	350	265	400	710	45	40	130	50	12x5	
KPR-2740	400	265	450	760	45	40	130	50	12x5	
KPR-2745	450	265	500	810	45	40	130	50	12x5	
KPR-3240	400	315	450	780	50	45	135	60	14x5.5	
KPR-3245	450	315	500	830	50	45	135	60	14x5.5	
KPR-3250	500	315	550	880	60	55	135	60	16x6	
KPR-3260	600	315	650	980	60	55	135	60	16x6	
KPR-3540C	400	350	450	790	55	50	140	60	16x6	300mT(3000 G)以上
KPR-3545C	450	350	500	850	55	50	140	70	16x6	
KPR-3550C	500	350	550	900	55	50	140	70	16x6	
KPR-3560C	600	350	650	1000	55	50	140	70	16x6	
KPR-4045C	450	400	500	860	60	55	145	70	16x6	
KPR-4050C	500	400	550	920	60	55	145	80	16x6	
KPR-4060C	600	400	650	1020	60	55	145	80	16x6	
KPR-4075C	750	400	820	1200	60	55	150	80	16x6	
KPR-5060C	600	500	650	1040	70	65	150	90	18x7	
KPR-5075C	750	500	820	1210	70	65	150	90	18x7	
KPR-5090C	900	500	1000	1400	70	65	150	100	18x7	
KPR-6075C	750	600	820	1300	75	70	190	100	20x7.5	
KPR-6090C	900	600	1000	1500	80	75	190	120	20x7.5	
KPR-60105C	1050	600	1150	1670	90	85	200	120	25x9	
KPR-60120C	1200	600	1300	1820	90	85	200	120	25x9	
KPR-7575C	750	750	820	1370	95	85	200	150	25x9	
KPR-75105C	1050	750	1150	1700	100	90	200	150	25x9	
KPR-75120C	1200	750	1300	1950	110	95	250	200	25x9	
KPR-75140C	1400	750	1500	2150	120	100	250	200	28x10	