

铁屑分离器





型号 | MS-BS

产地 | 日本·Kanetec

产品描述

用途 可安装到磨床的磨削液净化循环系统中，以去除铁粉
适用于磨削液中铁粉的去除

特点 订购MS-BS 系列时，请务必在型号名称中指定入口和排液口方向
也有高磁力型（稀土磁铁规格）

规格参数

| 型号 | 入口方向 | 出口方向 | 处理能力 (L/min) | 电源 | 电机功率 | 尺寸 (mm) | | | | | | | | | | | | | | | | | | | | | | | |
|-------------|------|------|-----------------|-------------------------|------|---------|-----|-----|-----|-----|----|------|-----|-----|------|-----|-----|-----|------|-----|------|-----|----|----|-----|-----|------|-----|------|
| | | | | | | L | B | H | L1 | L2 | L3 | L4 | e | P | P1 | P2 | B1 | b1 | b2 | b3 | H1 | H2 | H3 | H4 | M | D | D1 | d1 | D2 |
| MS-24B S-BL | ① | ④ | 240 | 三相 AC200V 50/60Hz | 90W | 670 | 645 | 534 | 620 | 90 | - | 25 | 25 | 570 | 572 | 495 | 515 | 615 | 80 | 386 | 268 | 189 | 77 | 17 | 214 | 102 | PS-3 | 127 | PS-4 |
| MS-24B S-BR | ① | ④ | | | | | | | | | - | 25 | | | | | | | | | | | | | | | | | |
| MS-24B S-RL | ② | ③ | | | | | | | | | 70 | - | | | | | | | | | | | | | | | | | |
| MS-24B S-RR | ② | ④ | | | | | | | | | 70 | - | | | | | | | | | | | | | | | | | |
| MS-36B S-BL | ① | ④ | 360 | 三相 AC200V 50/60Hz | 100W | 839 | | 50 | 105 | - | 35 | 730 | 630 | 668 | 790 | 345 | 100 | 127 | PS-4 | 154 | PS-5 | | | | | | | | |
| MS-36B S-BR | ① | ④ | | | | | | | | - | 35 | | | | | | | | | | | | | | | | | | |
| MS-36B S-RL | ② | ③ | | | | | | | | 80 | - | | | | | | | | | | | | | | | | | | |
| MS-36B S-RR | ② | ③ | | | | | | | | 80 | - | | | | | | | | | | | | | | | | | | |
| MS-50B S-BL | ① | ④ | 500 | | 830 | 670 | 780 | 120 | 120 | 120 | 35 | 1030 | 930 | 968 | 1090 | 358 | 115 | 154 | PS-5 | 182 | PS-6 | | | | | | | | |
| MS-50B S-BR | ① | ④ | | | | | | | | - | 35 | | | | | | | | | | | | | | | | | | |
| MS-50B S-RL | ② | ③ | | | | | | | | 90 | - | | | | | | | | | | | | | | | | | | |
| MS-50B S-RR | ② | ④ | | | | | | | | 90 | - | | | | | | | | | | | | | | | | | | |