

## 台型直角规



型号 | 546

产地 | 日本·RSK

## 产品描述

### 特点

尺寸精度：相当JIS B 7526  
由于直角尺带厚底座，确保了测量的稳定性  
所有1级品均经过淬火处理，增强测量面的耐磨性  
2级未经过热处理  
标有星号的尺寸都符合JIS规范  
可根据客户需求特殊定制

### 用途

用于检测工件的垂直度及工件相对位置的垂直度  
适用于机床、机械设备及零部件的垂直度检验，安装加工定位，划线等

## 规格参数

| 订货型号       | 尺寸 (mm) | 垂直度 (±μm) | 直线度 (±μm) | L (mm) | L1 (mm) | L2 (mm) | W (mm) | W1 (mm) | T (mm) | T1 (mm) | 重量 (kg) |
|------------|---------|-----------|-----------|--------|---------|---------|--------|---------|--------|---------|---------|
| 546-0050CQ | 50      | 12.5      | 6.2       | 50     | 40      | 38      | 14     | 13      | 10     | 2.5     | 0.05    |
| 546-0050C2 | 50      | 25.0      | 12.5      | -      | -       | -       | -      | -       | -      | -       | 0.05    |
| 546-0075CQ | *75     | 13.7      | 6.8       | 75     | 50      | 48      | 16     | 15      | 13     | 2.5     | 0.1     |
| 546-0075C2 | *75     | 27.5      | 13.7      | -      | -       | -       | -      | -       | -      | -       | 0.1     |
| 546-0100CQ | *100    | 15.0      | 7.5       | 100    | 70      | 67      | 20     | 18      | 15     | 2.5     | 0.18    |
| 546-0100C2 | *100    | 30.0      | 15.0      | -      | -       | -       | -      | -       | -      | -       | 0.18    |
| 546-0150CQ | *150    | 17.5      | 8.7       | 150    | 100     | 97      | 24     | 22      | 18     | 3       | 0.4     |
| 546-0150C2 | *150    | 35.0      | 17.5      | -      | -       | -       | -      | -       | -      | -       | 0.4     |
| 546-0200CQ | *200    | 20.0      | 10.0      | 200    | 130     | 126     | 29     | 26      | 22     | 4       | 0.74    |
| 546-0200C2 | *200    | 40.0      | 20.0      | -      | -       | -       | -      | -       | -      | -       | 0.74    |
| 546-0250CQ | 250     | 22.5      | 11.2      | 250    | 164     | 160     | 30     | 26      | 22     | 4       | 1.0     |
| 546-0250C2 | 250     | 45.0      | 22.5      | -      | -       | -       | -      | -       | -      | -       | 1.0     |
| 546-0300CQ | *300    | 25.0      | 12.5      | 300    | 200     | 196     | 35     | 32      | 27     | 4       | 1.7     |
| 546-0300C2 | *300    | 50.0      | 25.0      | -      | -       | -       | -      | -       | -      | -       | 1.7     |
| 546-0400CQ | 400     | 30.0      | 15.0      | 400    | 204     | 200     | 40     | 40      | 30     | 5       | 2.5     |
| 546-0400C2 | 400     | 60.0      | 30.0      | -      | -       | -       | -      | -       | -      | -       | 2.5     |
| 546-0450CQ | 450     | 32.5      | 16.2      | 450    | 280     | 276     | 45     | 40      | 30     | 5       | 3.2     |
| 546-0450C2 | 450     | 65.0      | 32.5      | -      | -       | -       | -      | -       | -      | -       | 3.2     |
| 546-0500CQ | *500    | 35.0      | 17.5      | 500    | 300     | 295     | 46     | 45      | 35     | 5       | 4.6     |
| 546-0500C2 | *500    | 70.0      | 35.0      | -      | -       | -       | -      | -       | -      | -       | 4.6     |
| 546-0600CQ | 600     | 40.0      | 20.0      | 600    | 325     | 318     | 50     | 55      | 35     | 6       | 6.7     |
| 546-0600C2 | 600     | 80.0      | 40.0      | -      | -       | -       | -      | -       | -      | -       | 6.7     |
| 546-0750CQ | *750    | 47.5      | 23.7      | 750    | 400     | 393     | 58     | 63      | 50     | 8       | 12.3    |
| 546-0750C2 | *750    | 95.0      | 47.5      | -      | -       | -       | -      | -       | -      | -       | 12.3    |
| 546-1000CQ | *1000   | 60.0      | 30.0      | 1000   | 550     | 540     | 65     | 80      | 65     | 10      | 29.6    |
| 546-1000C2 | *1000   | 120.0     | 60.0      | -      | -       | -       | -      | -       | -      | -       | 29.6    |
| 546-1500CQ | 1500    | 85.0      | 42.5      | 1500   | 620     | 607     | 80     | 90      | 65     | 10      | 38.0    |
| 546-1500C2 | 1500    | 170.0     | 85.0      | -      | -       | -       | -      | -       | -      | -       | 38.0    |
| 546-2000CQ | 2000    | 110.0     | 55.0      | 2000   | 830     | 815     | 100    | 105     | 70     | 12      | 66.7    |
| 546-2000C2 | 2000    | 220.0     | 110.0     | -      | -       | -       | -      | -       | -      | -       | 66.7    |

\*标有星号的尺寸都符合JIS规范。可根据客户需求特殊定制