

台型直角规



型号 | 546

产地 | 日本·RSK

产品描述

特点

尺寸精度：相当JIS B 7526
由于直角尺带厚底座，确保了测量的稳定性
所有1级品均经过淬火处理，增强测量面的耐磨性
2级未经过热处理
标有星号的尺寸都符合JIS规范
可根据客户需求特殊定制

用途

用于检测工件的垂直度及工件相对位置的垂直度
适用于机床、机械设备及零部件的垂直度检验，安装加工定位，划线等

规格参数

订货型号	尺寸 (mm)	垂直度 (±μm)	直线度 (±μm)	L (mm)	L1 (mm)	L2 (mm)	W (mm)	W1 (mm)	T (mm)	T1 (mm)	重量 (kg)
546-0050CQ	50	12.5	6.2	50	40	38	14	13	10	2.5	0.05
546-0050C2	50	25.0	12.5	-	-	-	-	-	-	-	0.05
546-0075CQ	*75	13.7	6.8	75	50	48	16	15	13	2.5	0.1
546-0075C2	*75	27.5	13.7	-	-	-	-	-	-	-	0.1
546-0100CQ	*100	15.0	7.5	100	70	67	20	18	15	2.5	0.18
546-0100C2	*100	30.0	15.0	-	-	-	-	-	-	-	0.18
546-0150CQ	*150	17.5	8.7	150	100	97	24	22	18	3	0.4
546-0150C2	*150	35.0	17.5	-	-	-	-	-	-	-	0.4
546-0200CQ	*200	20.0	10.0	200	130	126	29	26	22	4	0.74
546-0200C2	*200	40.0	20.0	-	-	-	-	-	-	-	0.74
546-0250CQ	250	22.5	11.2	250	164	160	30	26	22	4	1.0
546-0250C2	250	45.0	22.5	-	-	-	-	-	-	-	1.0
546-0300CQ	*300	25.0	12.5	300	200	196	35	32	27	4	1.7
546-0300C2	*300	50.0	25.0	-	-	-	-	-	-	-	1.7
546-0400CQ	400	30.0	15.0	400	204	200	40	40	30	5	2.5
546-0400C2	400	60.0	30.0	-	-	-	-	-	-	-	2.5
546-0450CQ	450	32.5	16.2	450	280	276	45	40	30	5	3.2
546-0450C2	450	65.0	32.5	-	-	-	-	-	-	-	3.2
546-0500CQ	*500	35.0	17.5	500	300	295	46	45	35	5	4.6
546-0500C2	*500	70.0	35.0	-	-	-	-	-	-	-	4.6
546-0600CQ	600	40.0	20.0	600	325	318	50	55	35	6	6.7
546-0600C2	600	80.0	40.0	-	-	-	-	-	-	-	6.7
546-0750CQ	*750	47.5	23.7	750	400	393	58	63	50	8	12.3
546-0750C2	*750	95.0	47.5	-	-	-	-	-	-	-	12.3
546-1000CQ	*1000	60.0	30.0	1000	550	540	65	80	65	10	29.6
546-1000C2	*1000	120.0	60.0	-	-	-	-	-	-	-	29.6
546-1500CQ	1500	85.0	42.5	1500	620	607	80	90	65	10	38.0
546-1500C2	1500	170.0	85.0	-	-	-	-	-	-	-	38.0
546-2000CQ	2000	110.0	55.0	2000	830	815	100	105	70	12	66.7
546-2000C2	2000	220.0	110.0	-	-	-	-	-	-	-	66.7

*标有星号的尺寸都符合JIS规范。可根据客户需求特殊定制