


扁平型直角规



型号 | 547

产地 | 日本·RSK

产品描述

特点

尺寸精度：相当JIS B 7526
直角规为平面，可以放平使用
所有1级品均经过淬火处理，增强测量面的耐磨性
2级未经过热处理
标有星号的尺寸都符合JIS规范
可根据客户需求特殊定制

用途

用于检测工件的垂直度及工件相对位置的垂直度
适用于机床、机械设备及零部件的垂直度检验，安装加工定位，划线等

规格参数

订货型号	尺寸 (mm)	垂直度 (±μm)	直线度 (±μm)	L (mm)	L1 (mm)	W (mm)	W1 (mm)	重量 (kg)
547-0050CQ	50	12.5	6.2	50	40	15	3	0.04
547-00502	50	25.0	12.5	-	-	-	-	0.04
547-0075CQ	*75	13.7	6.8	75	50	18	3	0.05
547-00752	*75	27.5	13.7	-	-	-	-	0.05
547-0100CQ	*100	15.0	7.5	100	70	25	4	0.08
547-01002	*100	30.0	15.0	-	-	-	-	0.08
547-0150CQ	*150	17.5	8.7	150	100	25	5	0.22
547-01502	*150	35.0	17.5	-	-	-	-	0.22
547-0200CQ	*200	20.0	10.0	200	130	25	6	0.35
547-02002	*200	40.0	20.0	-	-	-	-	0.35
547-0250CQ	250	22.5	11.2	250	165	30	6	0.54
547-02502	250	45.0	22.5	-	-	-	-	0.54
547-0300CQ	*300	25.0	12.5	300	200	30	6	0.66
547-03002	*300	50.0	25.0	-	-	-	-	0.66
547-0400CQ	400	30.0	15.0	400	200	40	8	1.4
547-04002	400	60.0	30.0	-	-	-	-	1.4
547-0450CQ	450	32.5	16.2	450	235	40	8	1.62
547-04502	450	65.0	32.5	-	-	-	-	1.62
547-0500CQ	*500	35.0	17.5	500	300	40	8	1.91
547-05002	*500	70.0	35.0	-	-	-	-	1.91
547-0600CQ	600	40.0	20.0	600	300	50	10	3.3
547-06002	600	80.0	40.0	-	-	-	-	3.3
547-0750CQ	*750	47.5	23.7	750	400	50	10	4.3
547-07502	*750	95.0	47.5	-	-	-	-	4.3
547-1000CQ	*1000	60.0	30.0	1000	550	60	12	8.4
547-10002	*1000	120.0	60.0	-	-	-	-	8.4
547-1500CQ	1500	85.0	42.5	1500	750	80	14	19.1
547-15002	1500	170.0	85.0	-	-	-	-	19.1
547-2000CQ	2000	110.0	55.0	2000	1000	100	16	36.3
547-20002	2000	220.0	110.0	-	-	-	-	36.3

*标有星号的尺寸都符合JIS规范。可根据客户需求特殊定制