



塑料固定盘抛光布轮

抛光布轮

耗材

研磨



型号 | 168 100F

产地 | 德国·Hatho

产品描述


特点 带铁芯的塑料盘，可以更方便的固定在打磨机器的主轴上
抛光布轮适用转速建议在1400rpm
塑料固定盘中心孔为 $\phi 6\text{mm}$










用途 工件的研磨抛光










规格参数

如下表图型所示：

对应不同的材质、型号，其中 ϕ 为抛光布轮的直径；B为塑料固定盘的直径，F为布轮的厚度，LZ为层数。（尺寸单位mm）

外形样式	材质	型号	ϕ	B	F	LZ
	百褶纱布轮	165 100 Pli	100	45	18	
	微褶纱布轮	166 100 F	100	43	16	
		168 100 F	100	43	16	
	微褶绒布轮	168 80 F	80	43	16	
	绒布轮	161 100/20	100	40	17	20
	羊毛布轮	162 100/5	100	40	18	6
	高级棉布轮	163 100/40	100	40	16	40
	纱布轮	164 100/20	100	40	15	20
		164 100/40	100	40	18	40
		164 100/55	100	40	20	55
		50 100/7	100	40	16	7

	鹿皮轮	50 80/7	400	40	19	7
	鹿皮条轮	500 90 LE	90	40	18	
	超细纤维皮轮	520 100/7	100	40	15	7
	超细纤维皮条轮	520 90 LE	90	40	18	
	超细纤维布	820 100/15	100	40	15	15
	软质硅涂层棉布轮	869 100/14	100	40	10	14
		869 100/20	100	40	13	20
		869 100/28	100	40	20	28
	硅涂层棉布轮	870 100/14	100	40	12	14
		870 100/22	100	40	20	22
	高密度纯棉布轮	873 125X24K	125	51	24	
		873 125X30K	125	51	30	
		163 125X24K	125	51	24	
	高级纯棉布轮	163 125X30K	125	51	30	
		161 125X24K	125	51	24	

	软棉织布轮	161 125X30K	125	51	30	
		162 125X24K	125	51	24	
	羊毛毡轮	162 125X30K	125	51	30	
		520 125X24K	125	51	24	
	超细纤维皮轮	520 125X30K	125	51	30	
		160 125X24K	125	51	24	
	粗棉布轮	160 125X30K	125	51	30	
		869 125X24K	125	51	24	
	软质硅涂层棉布轮	869 125X30K	125	51	30	
		870 125X24K	125	51	24	
	硅涂层棉布轮	870 125X30K	125	51	30	
		169 125/90K	125	51	19	90
	多层布	169 150/90K	150	51	19	90
		167 100/10K	100	42	10	10
	微褶纱布轮	167 100/20K	100	42	22	20
		167 100/30K	100	51	33	30
		862 125X20K	125	50	20	50
	超细纤维布轮					