

## 拉力测试棒



**BESTOOL-KANON**  
 器中村製作所

型号 | TK

产地 | 日本·Kanlon

### 产品描述

#### 特点

利用弹簧力进行精确测量，以圆柱形式显示刻度  
若在水平方向使用,请根据表格的偏差值加到实际测量值中  
需要置针型，订购时请注明TK-G  
保证精度： $\pm 1$  刻度

#### 用途

用测量推力、拉力和弹簧张力

## 规格参数

| 型号      | 调整范围<br>(g) | 最小读值<br>(g) | A   | B  | C  | D   | E   | F    | G   | H  | I    | L   | 水平时偏<br>差 (g) |
|---------|-------------|-------------|-----|----|----|-----|-----|------|-----|----|------|-----|---------------|
| TK10    | 0-10        | 0.5         | 1.5 | 16 | 13 | 1.5 | 40  | 19   | 98  | 15 | 48   | 180 | 3             |
| TK30    | 0-30        | 1           | 1.5 | 16 | 13 | 1.5 | 60  | 19   | 113 | 15 | 66   | 213 | 3             |
| TK50    | 0-50        | 1           | 1.5 | 16 | 13 | 1.5 | 60  | 19   | 113 | 15 | 66   | 213 | 3             |
| TK110   | 0-110       | 2           | 2   | 16 | 13 | 2   | 60  | 27.5 | 113 | 15 | 65.5 | 221 | 10            |
| TK200   | 0-200       | 5           | 2   | 16 | 13 | 2   | 60  | 27.5 | 113 | 15 | 65.5 | 221 | 10            |
| TK300   | 0-300       | 5           | 2   | 16 | 13 | 2   | 60  | 27.5 | 113 | 15 | 65.5 | 221 | 10            |
| TK500   | 0-500       | 10          | 3   | 20 | 16 | 2.6 | 56  | 43   | 131 | 25 | 69   | 268 | 30            |
| TK600   | 0-600       | 20          | 3   | 20 | 16 | 2.6 | 56  | 43   | 131 | 23 | 69   | 268 | 30            |
| TK1000  | 0-1000      | 25          | 3   | 20 | 16 | 2.6 | 56  | 43   | 131 | 23 | 69   | 268 | 30            |
| TK1500  | 0-1500      | 50          | 3   | 20 | 16 | 2.6 | 56  | 43   | 131 | 23 | 69   | 268 | 30            |
| TK2000  | 0-2000      | 50          | 3   | 20 | 16 | 2.6 | 56  | 43   | 131 | 23 | 69   | 268 | 30            |
| TK2500  | 0-2500      | 50          | 3   | 20 | 16 | 2.6 | 62  | 43   | 143 | 25 | 74   | 285 | 50            |
| TK3000  | 0-3000      | 50          | 3   | 20 | 16 | 2.6 | 62  | 43   | 143 | 25 | 74   | 285 | 50            |
| TK4000  | 0-4000      | 50          | 4   | 25 | 22 | 3.5 | 68  | 43   | 178 | 35 | 82   | 338 | 100           |
| TK5000  | 0-5000      | 100         | 4   | 25 | 22 | 3.5 | 68  | 43   | 178 | 35 | 82   | 338 | 100           |
| TK7000  | 0-7000      | 200         | 4   | 25 | 22 | 3.5 | 68  | 43   | 178 | 35 | 82   | 338 | 100           |
| TK10000 | 0-10000     | 200         | 4   | 25 | 22 | 3.5 | 68  | 43   | 178 | 35 | 82   | 338 | 100           |
| TK15000 | 0-15000     | 200         | 8   | 35 | 32 | 7   | 95  | 83   | 230 | 35 | 145  | 493 | 250           |
| TK20000 | 0-20000     | 200         | 8   | 35 | 32 | 7   | 118 | 83   | 280 | 35 | 140  | 538 | 250           |
| TK30000 | 0-30000     | 500         | 8   | 40 | 38 | 7   | 130 | 83   | 305 | 35 | 172  | 595 | 350           |

## 规格参数

| 型号        | 调整范围<br>(g) | 最小读值<br>(g) | A   | B  | C  | D   | E   | F    | G   | H  | I    | L   | 水平时偏<br>差 (g) |
|-----------|-------------|-------------|-----|----|----|-----|-----|------|-----|----|------|-----|---------------|
| TK10cN    | 0-10        | 0.5         | 1.5 | 16 | 13 | 1.5 | 40  | 19   | 98  | 15 | 48   | 180 | 3             |
| TK30cN    | 0-30        | 1           | 1.5 | 16 | 13 | 1.5 | 60  | 19   | 113 | 15 | 66   | 213 | 3             |
| TK50cN    | 0-50        | 1           | 1.5 | 16 | 13 | 1.5 | 60  | 19   | 113 | 15 | 66   | 213 | 3             |
| TK110cN   | 0-110       | 2           | 2   | 16 | 13 | 2   | 60  | 27.5 | 113 | 15 | 65.5 | 221 | 10            |
| TK200cN   | 0-200       | 5           | 2   | 16 | 13 | 2   | 60  | 27.5 | 113 | 15 | 65.5 | 221 | 10            |
| TK300cN   | 0-300       | 5           | 2   | 16 | 13 | 2   | 60  | 27.5 | 113 | 15 | 65.5 | 221 | 10            |
| TK500cN   | 0-500       | 10          | 3   | 20 | 16 | 2.6 | 56  | 43   | 131 | 23 | 69   | 268 | 30            |
| TK600cN   | 0-600       | 20          | 3   | 20 | 16 | 2.6 | 56  | 43   | 131 | 23 | 69   | 268 | 30            |
| TK1000cN  | 0-1000      | 25          | 3   | 20 | 16 | 2.6 | 56  | 43   | 131 | 23 | 69   | 268 | 30            |
| TK1500cN  | 0-1500      | 50          | 3   | 20 | 16 | 2.6 | 56  | 43   | 131 | 23 | 69   | 268 | 30            |
| TK2000cN  | 0-2000      | 50          | 3   | 20 | 16 | 2.6 | 56  | 43   | 131 | 23 | 69   | 268 | 30            |
| TK2500cN  | 0-2500      | 50          | 3   | 20 | 16 | 2.6 | 62  | 43   | 143 | 25 | 74   | 285 | 50            |
| TK3000cN  | 0-3000      | 50          | 3   | 20 | 16 | 2.6 | 62  | 43   | 143 | 25 | 74   | 285 | 50            |
| TK4000cN  | 0-4000      | 50          | 4   | 25 | 22 | 3.5 | 68  | 43   | 178 | 35 | 82   | 338 | 100           |
| TK5000cN  | 0-5000      | 100         | 4   | 25 | 22 | 3.5 | 68  | 43   | 178 | 35 | 82   | 338 | 100           |
| TK7000cN  | 0-7000      | 200         | 4   | 25 | 22 | 3.5 | 68  | 43   | 178 | 35 | 82   | 338 | 100           |
| TK10000cN | 0-10000     | 200         | 4   | 25 | 22 | 3.5 | 68  | 43   | 178 | 35 | 82   | 338 | 100           |
| TK15000cN | 0-15000     | 200         | 8   | 35 | 32 | 7   | 95  | 83   | 230 | 35 | 145  | 493 | 250           |
| TK20000cN | 0-20000     | 200         | 8   | 35 | 32 | 7   | 118 | 83   | 280 | 35 | 140  | 538 | 250           |
| TK30000cN | 0-30000     | 500         | 8   | 40 | 38 | 7   | 130 | 83   | 305 | 35 | 172  | 595 | 350           |