


梅花头扭力扳手(单能型)



型号 | RSPK

产地 | 日本·Kanon

产品描述

特点

多用于生产线上锁紧大量同样扭力的相同螺栓(螺母)无需刻度确认
更有效的应用于狭窄场合，例如机器的间隙
只能按箭头方向转动
设定扭力值需专用的扭力测试仪和调整工具，订货时需注明设定扭力值
精度：±3%以内

用途

用于拧紧螺丝，棘轮扳手头可提高效率，适合在生产线上大量锁定扭力且精度要求高的重复工作

规格参数

型号	扭力值	型号	扭力值	扭力扳手 开口尺寸 (W)				全长	主要尺寸 (mm)					
公制	Kgf · cm	牛顿	N · m	mm				mm	S	T	G	A	B	C
30RSPK	5-35	N3.5RSPK	0.5-3.5	5.5	6			175				19.5	7.5	15
				7	8	9	10							
80RSPK	20-90	N9SPK	2-9	5.5	6	7		197				19.5	7.5	15
				8	9	10								
				11	12									
190RSPK	40-210	N21RSPK	4-21	10				222				19.5	7.5	15
				11	12	13	14	225						
				17	19	22		228						
380RSPK	90-420	N42SPK	9-42	11	12	13	14	268	22	10	25	26.6	8.2	20
				17	19	21		273	32	10				
670RSPK	140-730	N73RSPK	14-73	14	17			343	26	12	27	25.8	9.7	20
				19	22	24		348	34	12				
				27	30	32		353	40	12				
				19				413	32	13				
1200RSPK	250-1270	N127RSPK	25-127	22	24			415	37	13	29	32.8	11.3	25
				27	30	32		428	44	13				
				36				437	50	13				
1600RSPK	320-1700	N170RSPK	32-170	19	22	24		470	37	15	31	32.8	11.3	25
				27	30	32		474	44	15				
2200RSPK	480-2300	N230RSPK	48-230	19				605	37	16.5	33	35.6	12.5	27.2
				22	24	27		608	41	16.5				
				30	32			610	46	16.5				
				36				612	50	16.5				
3100RSPK	680-3200	N320RSPK	68-320	41				612	54	16.5	35	38	16	30
				22				682	40	18				
				24	27	30		685	46	18				
				32	36			688	52	18				
4200RSPK	950-4300	N430RSPK	95-430	41				688	56	18	37	43.3	17.8	34
				27	30	32		880	52	18				
				36				885	55	18				
				41				890	60	18				
				46				895	65	18				

规格参数

型号	可用尺寸	尺寸 (mm)		型号	可用尺寸	尺寸 (mm)		型号	可用尺寸	尺寸 (mm)	
	mm	S	T		mm	S	T		mm	S	T
30RSPK N3.5RSPK	5.5	10	4	80RSPK N9SPK	5.5	10	4	190RSPK N21RSPK	10	16	7
	6	10	5		6	10	5		11	18	7
	7	10	6		7	10	6		12	19	8
	8	13	6		8	13	6		13	20	8.5
	9	14	6		9	14	6		14	22	9
	10	16	7		10	16	7		17	26	10
				11	18	7	19	29	10.5		
				12	19	8	22	33	12		